Reply to Office Action of September 15, 2010

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:** 

1. (Currently Amended) A device for supplying that supplies mixed gas to radiant

heating type gas burners of radiant heating type having a housing, a plurality of burner

assemblies in the housing for combustion of the mixed gas therein, each with of the plurality of

burner assemblies having a burner chamber for supplying mixed gasthat receives a mixture of

fuel gas and air theretotherein, and a glass plate placed on top of the housing, comprising:

a plurality of mixing tubes respectively in communication with the plurality of burner

chambers for supplying the fuel gas and the-air thereto;

a plurality of gas nozzles for respectively spraying the fuel gas into the plurality of mixing

tubes;

a plurality of air supply tubes each spaced a distance away from the other end of one of

the mixing tubes, for supplying for respectively directing air toward the one-plurality of the

mixing tubes, wherein a first end of each of the plurality of mixing tubes is coupled to a

corresponding burner chamber and a first end of each of the plurality of air supply tubes is

axially aligned with a second end of a corresponding mixing tube, with a predetermined gap

formed therebetween;

2

Reply to Office Action of September 15, 2010

a plurality of air passages defined by the predetermined gaps formed between the air supply tubes and the mixing tubes, wherein outside air is drawn through the plurality of air passages and into the plurality of mixing tubes by a pressure difference between the outside and inside of the mixing tubes; and

a at least one fan unit connected to anin communication with a second end of at least one of the plurality of air supply tubes for supplying air thereto.

- 2. (Currently Amended) The device as claimed in claim 1, wherein the predetermined gap formed between the first end of each air supply tube has one end spaced from the other and the second end of the respective mixing tube in formed in a radial direction.
- 3. (Currently Amended) The device as claimed in claim 1, wherein the predetermined gap formed between the first end of each air supply tube has one end spaced from the otherand the second end of the respective mixing tube is formed in a length longitudinal direction.
- 4. (Currently Amended) The device as claimed in claim 1, wherein the <u>at least one</u> fan <u>unit</u> is <u>on provided at an outside of the housing.</u>

5. (Currently Amended) The device as claimed in claim 1, further comprising at least one air supply chamber <u>formed</u> between the <u>plurality of air supply tubes and the <u>at least one</u> fan <u>unit for receivingso as to provide</u> air from the <u>at least one</u> fan <u>unit and supplying the air to the plurality of air supply tubes.</u></u>

## 6. (Cancelled)

- 7. (Currently Amended) The device as claimed in claim 1, further comprising at least one branch tube having one a first end connected to the at least one fan unit, and the othera second end connected to a in communication with the plurality of the air supply tubes for distributingso as to distribute air from the at least one fan unit to the plurality of air supply tubes.
- 8. (Currently Amended) The device as claimed in claim 1, further comprising a plurality of connecting member for connecting the members that each connect a mixing tube of the plurality of mixing tubes to the a corresponding air supply tube-together.
- 9. (Currently Amended) The device as claimed in claim 8, wherein <u>each of the plurality of connecting member members includes a nozzle holding member formed as a unit for holding the that holds a corresponding gas nozzle of the plurality of gas nozzles.</u>

Reply to Office Action of September 15, 2010

- 10. (Currently Amended) The device as claimed in claim 8, wherein the connecting member is fixed to opposite sides of the further comprising a fastening device that fastens each connecting member to a respective mixing tube and the air supply tube with fastening means.
- 11. (Currently Amended) The device as claimed in claim 8, wherein the each mixing tube, the corresponding air supply tube, and the corresponding connecting member form a mixing tube assembly having two symmetric members bonded together.
- 12. (Currently Amended) The device as claimed in claim 11, wherein the mixing tube assembly includes; comprises:

a first mixing tube assembly having a first mixing tube part forming a first half of the mixing tube, a first air supply tube part forming a first half of the air supply tube, and a plate form of secondshaped first connection member extended that extends outward from both two opposite sides of the first mixing tube part and the first air supply part as one a single unit so as to connect the first mixing tube part and the first air supply part as one a single unit; and

a second mixing tube assembly having a second mixing tube part forming a second half of the mixing tube, a second air supply tube part forming a second half of the air supply tube, and a plate form of shaped second connection member extended that extends outward from both two opposite sides of the second mixing tube part and the second air supply part as one a single unit so as to connect the second mixing tube part and the second air supply part as one a

Reply to Office Action of September 15, 2010

single unit, and wherein the second connection member is bonded with the first connection

member.

13. (Currently Amended) The device as claimed in claim 8, wherein the each mixing

tube, the corresponding air supply tube, and the corresponding connecting member are injection

molded as one a single unit.

14. (Currently Amended) The device as claimed in claim 1, wherein the a sectional

area of the first end of each air supply tube has the other end, facing the other second end of the

respective mixing tube, with a sectional area equal to, or is greater than or equal to a sectional

area of the other-second end of the respective mixing tube.

15. (Currently Amended) The device as claimed in claim 1, wherein a diameter of the

first end of each air supply tube has the other end facing the other second end of the respective

mixing tube with a diameter becoming is greater than a diameter of other part portions of the air

supply tube so as to have an expanded tube form.

16. (Currently Amended) The device as claimed in claim 1, wherein the at least one

fan unit-includes; a fan, and a variable speed motor for varying that varies a rotation speed of the

Serial No. 10/584,891

Amendment dated **December 15, 2010** 

Reply to Office Action of September 15, 2010

at least one fan according to based on a gas spray rate through the one or more of the plurality of gas nozzlenozzles.

- 17. (Currently Amended) The device as claimed in claim 1, wherein each one of the plurality of mixing tubes is connected to a plurality of air supply tubes for supplying air thereto.
- 18. (Currently Amended) A device for supplying that supplies mixed gas to radiant heating type gas burners of radiant heating type having a housing, a plurality of burner assemblies provided in the housing for combustion of the mixed gas therein, each with of the plurality of burner assemblies having a burner chamber for supplying mixed gas that receives a mixture of fuel gas and air theretotherein, and a glass plate placed on top of positioned on the housing, comprising:

a plurality of mixing tubes respectively in communication with the <u>plurality of burner</u> chambers for supplying the fuel gas and the air thereto;

a plurality of gas nozzles for respectively spraying the fuel gas into their communication with the plurality of mixing tubes;

a plurality of air supply tubes each spaced a <u>predetermined</u> distance <u>away apart</u> from the <u>other and axially aligned with a corresponding end of onea respective mixing tube</u> of the <u>plurality</u> <u>of mixing tubes</u>;

Reply to Office Action of September 15, 2010

a plurality of air passages defined by predetermined gaps formed between the air supply tubes and the mixing tubes, wherein outside air is drawn through the plurality of air passages and into the plurality of mixing tubes by a pressure difference between the outside and inside of the mixing tubes;

a <u>at least one</u> fan <u>unit for supplying that supplies</u> air to the <u>plurality of</u> air supply tubes; and

at least one air supply chamber <u>provided</u> between the <u>plurality of</u> air supply tubes and the <u>at least one</u> fan <u>unit for receivingso as to direct</u> air from the fan <u>unit and supplying the air</u> to the <u>plurality of</u> air supply tubes.

- 19. (Original) The device as claimed in claim 18, wherein the air supply chamber is integrated inside of the housing.
- 20. (Original) The device as claimed in claim 18, wherein the air supply chamber has a plurality of air supply tubes of other burner assemblies connected thereto.
- 21. (Currently Amended) A device for supplying that supplies mixed gas to radiant heating type gas burners of radiant heating type having a housing, a plurality of burner assemblies provided in the housing for combustion of the mixed gas therein, each with of the plurality of burner assemblies having a burner chamber for supplying mixed gas that receives a

Serial No. **10/584,891** 

Amendment dated December 15, 2010

Reply to Office Action of September 15, 2010

mixture of fuel gas and air theretotherein, and a glass plate placed on top of positioned on the housing, comprising:

a plurality of mixing tubes respectively in communication with the <u>plurality of burner</u> chambers for supplying the fuel gas and the air thereto;

a plurality of gas nozzles for respectively spraying thein communication with the plurality of mixing tubes so as to spray fuel gas into the mixing tubes therein;

a plurality of air supply tubes each having one end spaced a <u>predetermined</u> distance away apart from the other and axially aligned with a corresponding end of one a respective mixing tube of the <u>plurality of mixing tubes</u>;

a fan unit for supplying air in communication with the plurality of air supply tubes; and at least one branch tube having one a first end connected to the fan unit, and the othera second end connected to a the plurality of the air supply tubes for distributingso as to distribute air from the fan unit to the plurality of air supply tubes.

22. (Currently Amended) A device for supplying that supplies mixed gas to gas burners of radiant heating type having a housing, a plurality of burner assemblies provided in the housing for combustion of the mixed gas therein, and each with having a burner chamber for supplying mixed gas that receives a mixture of fuel gas and air theretotherein, and a glass plate placed on top of positioned the housing, comprising:

a mixing tube assembly, including;:

a mixing tube having one end in communication with the burner chamber for supplyingso as to supply fuel gas and air to the burner chamber;

an air supply tube formed as one unit with the mixing tube onpositioned at an outside of the mixing tube such that one an end thereof is spaced a predetermined distance away apart from the other a corresponding end of the mixing tube for supplying in a radial direction air to the mixing tube;

an air passage formed between the corresponding ends of the air supply tube and the mixing tube, wherein a pressure difference between the outside and an interior of the mixing tube draws air into the mixing tube through the air passage; and

a connecting member for connecting that connects the mixing tube and the air supply tube as one so as to form a single unit;

a gas nozzle at a position-spaced a <u>predetermined</u> distance away apart from the mixing tube for sprayingso as to spray gas toward the mixing tube; and

a fan unit for blowing that blows air to into the air supply tube.

23. (Original) The device as claimed in claim 22, wherein the connecting member includes a nozzle holding part for holding the gas nozzle.

Reply to Office Action of September 15, 2010

24. (Currently Amended) The device as claimed in claim 22, wherein further comprising a fastening device that fixes the connecting member is fixed to opposite side parts of the mixing tube and the air supply tube with fastening means.

25. (Currently Amended) The device as claimed in claim 22, wherein the mixing tube assembly includes; comprises:

a first mixing tube assembly having a first mixing tube part forming a first half of the mixing tube, a first air supply tube part forming a first half of the air supply tube, and a plate form of secondshaped first connection member extended that extends outward from both two opposite sides of the first mixing tube part and the first air supply part as one a single unit so as to connect the first mixing tube part and the first air supply part as one a single unit; and

a second mixing tube assembly having a second mixing tube part forming a second half of the mixing tube, a second air supply tube part forming a second half of the air supply tube, and a plate form of shaped second connection member extended that extends outward from both two opposite sides of the second mixing tube part and the second air supply part as one a single unit so as to connect the second mixing tube part and the second air supply part as one a single unit, and wherein the second connection member is bonded with the first connection member.

Reply to Office Action of September 15, 2010

26. (Currently Amended) The device as claimed in claim 22, wherein the mixing tube assembly is formed as one a single unit by injection molding.

- 27. (Currently Amended) The device as claimed in claim 22, wherein a sectional area of the one end of the air supply tube facing the other corresponding end of the mixing tube has a sectional area of the other corresponding end of the mixing tube.
- 28. (Currently Amended) The device as claimed in claim 122, wherein a diameter of the one end of the air supply tube facing the other corresponding end of the mixing tube has a diameter becoming greater than a diameter of other part to have portions thereof such that the air supply tube has an expanded tube form.